

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 10 N., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 10 N R 5 W
S 26
1/4 S 35
1988

Bury the mkd. stone alongside the stainless steel post and raise a mound of stone, N of the cor.

N. 89° 52.2' W., beginning new measurement.

Over nearly level mud flats.

40.106

The cor. of secs. 26, 27, 34, and 35, monumented with a limestone, 18x14x14 ins., lying loose on the surface, with a steel fence post, projecting 5 ft. above ground alongside. No marks visible.

At the corner point

Set a plastic post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 10 N R 5 W
S 27 | S 26
S 34 | S 35
1988

Bury the unmkd. stone alongside the plastic post.

N. 0° 14.4' E., bet. secs. 26 and 27.

Over nearly level mud flats.

40.259

Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 10 N R 5 W
1/4
S 27 | S 26
1988

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 10 N., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.

80.518 The cor. of secs. 22, 23, 26, and 27, monumented with a limestone, 16x16x8 ins., lying loose on the surface. No marks visible.

At the corner point

Set a plastic post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 10 N R 5 W			
S 22		S 23	
S 27		S 26	
1988			

Bury the unmkd. stone alongside the plastic post.

From the cor. of secs. 23, 24, 25, and 26.

S. 89° 51.2' W., bet. secs. 23 and 26.

Over nearly level mud flats and sand hills with sparse to moderate sagebrush, greasewood, and grasses.

39.905 The 1/4 sec. cor. of secs. 23 and 26, monumented with a limestone, 13x8x6 ins., loosely set, mkd. 1/4 on N face.

At the corner point

Set a plastic post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 10 N R 5 W			
		S 23	
1/4	S 26		
1988			

Bury the mkd. stone alongside the plastic post and raise a mound of stone, N of the cor.

S. 89° 57.4' W., beginning new measurement.

Over nearly level mud flats and sand hills with sparse to moderate sagebrush, greasewood, and grasses.

39.959 The cor. of secs. 22, 23, 26, and 27.

N. 0° 15.3' W., bet. secs. 22 and 23.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL,
LINES, T. 10 N., R. 5 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over gently rolling sand hills with sparse to moderate sagebrush, greasewood, and grasses.

- 40.193** Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 10 N R 5 W
1/4
S 22 | S 23
1988

- 80.386** The cor. of secs. 14, 15, 22, and 23, monumented with a limestone, 17x10x10 ins., lying loose on the surface. No marks visible.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 N R 5 W
S 15 | S 14
S 22 | S 23
1988

Bury the unmkd. stone alongside the stainless steel post.

From this cor., the cor. of fences, bearing N and W, bears S. 36° 44.0' W., 3.658 chs. dist.

From the cor. of secs. 13, 14, 23, and 24.

N. 89° 56.8' W., bet. secs. 14 and 23.

Over nearly level mud flats and swampy areas with sparse to moderate marsh grasses.

- 40.158** The 1/4 sec. cor. of secs. 14 and 23, monumented with a limestone, 24x18x12 ins., loosely set, mkd. 1/4 on the N face.

At the corner point

Set a plastic post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap mkd.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 10 N., R. 5 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

T 10 N R 5 W

S 14

1/4 S 23

1988

Bury the mkd. stone alongside the plastic post.

N. 89° 51.1' W., beginning new measurement.

Over nearly level swampy lands with sparse to moderate marsh grasses.

40.110 The cor. of sec. 14, 15, 22, and 23.

From the cor. of secs. 22, 23, 26, and 27.

S. 89° 17.1' W., bet. secs. 22 and 27.

Over nearly level mud flats.

40.398 Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 10 N R 5 W

S 22

1/4 S 27

1988

80.796 The cor. of secs. 21, 22, 27, and 28, monumented with a limestone, 18x10x9 ins., firmly set. No marks visible.

Set a plastic post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 10 N R 5 W

S 21 | S 22

S 28 | S 27

1988

Bury the unmkd. stone and set a 4x4 ins. wood post, projecting 4 ft. above the ground, alongside the plastic post.

N. 0° 11.4' W., bet. secs. 21 and 22.

Over nearly level mud flats and sand hills with sparse to moderate sagebrush, greasewood, and grasses.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 10 N., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.160**

The 1/4 sec. cor. of secs. 21 and 22, monumented with a limestone, 20x18x6 ins., lying loose. No marks visible.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 N R 5 W

1/4
S 21 | S 22
1988

Bury the unmkd. stone alongside the plastic post.

N. 1° 37.1' E., beginning new measurement.

Over nearly level mud flats and sand hills with sparse to moderate sagebrush, greasewood, and grasses.

41.337

The cor. of secs. 15, 16, 21, and 22, monumented with a limestone, 14x7x5 ins., loosely set. No marks visible.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 N R 5 W

S 16 | S 15
S 21 | S 22
1988

Bury the unmkd. stone alongside the stainless steel post.

From this cor., the intersection of fences, bearing N. 5° W. and N. 88° E., bears S. 0° 09.4' E., 5.756 chs. dist.

From the cor. of secs. 14, 15, 22, and 23.

S. 88° 53.8' W., bet. secs. 15 and 22.

Over nearly level swampy lands with sparse to moderate marsh grasses.

40.314

The 1/4 sec. cor. of secs. 15 and 22, monumented with a limestone, 15x6x5 ins., loosely set. No marks visible.

At the corner point

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 10 N., R. 5 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a plastic post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 10 N R 5 W
 S 15
 1/4 S 22
 1988

Bury the unmkd. stone alongside the plastic post.

Cor. falls 3.500 chs. N of a fence line, bearing N. 88° E. and S. 88° W.

N. 88° 44.0' W., beginning new measurement.

Over nearly level swampy lands with sparse to moderate marsh grasses.

39.102 The cor. of secs. 15, 16, 21, and 22.

General Description

The lands resurveyed in T. 10 N., R. 5 W., are located approximately 10 miles west of Corinne, Utah, and consist of nearly level mud flats and swampy areas with some small sandy hills and ridges which are covered with sparse to moderate growths of sagebrush, greasewood, and grasses. Access to the general area is by way of Utah State Highway 83 which runs north of the lands surveyed and a dirt road which runs along the west boundary of section 22. The actual sections resurveyed are accessible only by foot or 4-wheel recreational vehicles because of numerous muddy areas. These lands are very wet and muddy in the springtime but gradually dry out so that by mid-summer, almost all muddy areas would be dry, making access much easier.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ronald K. Baugh Gregg Ostergaard	Cadastral Surveyor Surveying Technician

CERTIFICATE OF SURVEY

I, *Milbert H. Krohn, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *15th day of November, 1987*, I have *dependently resurveyed a portion of the south and east boundaries, and a portion of the subdivisional lines in Township 10 North, Range 5 West,*

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

10/30/89

Date

Milbert H. Krohn

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the south and east boundaries, and a portion of the subdivisional lines, Township 10 North, Range 5 West, Salt Lake Meridian, Utah,*

executed by *Milbert H. Krohn, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

December 18, 1989

Date

Milton R. Warkentin

(Chief Cadastral Surveyor, Utah State Office)

acting

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE WEST BOUNDARY

AND A

PORTION OF THE SUBDIVISIONAL LINES

AND THE SURVEY OF THE SUBDIVISION OF SECTION 31

AND

TRACT 37

IN

TOWNSHIP 13 NORTH, RANGE 13 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

RICHARD A. ZANINOVICH
CADASTRAL SURVEYOR

Under special instructions dated *November 4, 1988*, approved *November 8, 1988*, which provided for the surveys included under Group Number 729, and assignment instructions dated *November 8, 1988*.

Survey commenced *May 16, 1989*

Survey completed *May 23, 1989*

INDEX DIAGRAM

Township 13 North , Range 13 West

	6	5	4	3	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	24
	30 3	29	28	27	26	25
2	31 3	32	33	34	35	36

The Survey of the Subdivision of Section 31.....Page 4

The Survey of Tract 37.....Page 5

TOWNSHIP 13 NORTH, RANGE 13 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines and the survey of the subdivision of section 31, and tract 37 , in T. 13 N., R. 13 W., Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed byNORTH BOUNDARY

All	A.P. Hansen	1893
-----	-------------	------

SOUTH BOUNDARY (3rd Standard Parallel South)

All	G.V.M. Boutelle	1872	
Portion			F. Profaizer 1983

EAST BOUNDARY

Portion	G.V.M. Boutelle	1872
Portion	A.P. Hansen	1893

WEST BOUNDARY

Portion	G.V.M. Boutelle	1872
Portion	A.P. Hansen	1893

SUBDIVISION

Portion	G.V.M. Boutelle	1872
Portion	A.P. Hansen	1893

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the special instructions for Group No. 729, Utah, dated November 4, 1988.

The directions of lines were determined by references to true meridians established on line by hour angle observations on the sun. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions. Lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The N.A.D. 1927 geographic coordinates of the southeast corner of section 31, as calculated from 1983 resurvey data of T. 12 N., R. 14 W., is as follows:

TOWNSHIP 13 NORTH, RANGE 13 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Latitude: $41^{\circ} 48' 07.66''$ N. Longitude: $113^{\circ} 22' 02.71''$ W.

The mean magnetic declination as projected from U.S. Geological Survey "Magnetic Declination Map 1980" is $15 \frac{1}{2}^{\circ}$ E.

Dependent Resurvey of a Portion of the West Boundary,
T. 13 N., R. 13 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
G.V.M. Boutelle in 1872

Beginning at the standard cor. of T. 13 N., Rs. 13 and 14 W., monumented with an aluminum post, 2 1/2 ins. diam. projecting 6 ins. above ground with aluminum cap mkd. as described in the official record of the 1983 resurvey, executed by F.C. Profaizer. Cor. is set at the cor. of fences projecting N. and W.

N. $0^{\circ} 34'$ W., bet. secs. 31 and 36.

39.81

Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 in the ground, with aluminum cap, mkd.

T 13 N
R 14 W R 13 W
1/4
S 36 | S 31
1988

Cor. is located 5 lks. W. of N-S fence.

Raised a mound of stone W. of cor.

57.12

Point for cor. 3 of tract 37, hereinafter described.

67.12

Point for cor. 2 of tract 37, hereinafter described.

79.62

Point for the cor. of secs. 25, 30, 31, and 36, determined at the projected intersection of the fence bet. secs. 31 and 36, and the centerline of Utah State Highway No. 30.

Set a PK nail flush with the surface of the road.

**DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 13 N., R. 13 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

from which

An iron post, 2 1/2 ins. diam., set in concrete, 18 lks. S. of right-of-way fence, with standard Utah State Highway brass cap, bears N. $76^{\circ} 30'$ W., 3.055 chs. dist.

An iron post, 2 1/2 ins. diam., set in concrete, 1 lk. N. of right-of-way fence, with standard Utah State Highway brass cap, bears S. $74^{\circ} 48'$ W., 3.055 chs. dist.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 N., R. 13 W., Salt Lake Meridian, Utah.

From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap, mkd. as described in the official record of the 1983 resurvey, executed by F.C. Profaizer.

N. $0^{\circ} 55'$ W., bet. secs. 31 and 32.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 13 N R 13 W
1/4
S 31 | S 32
1989

Set a cedar post and raised a mound of stone W. of aluminum post.

80.00

Point for the cor. of secs. 29, 30, 31 and 32, as determined from Utah Department of Transportation records at the centerline of Utah State Highway No. 30.

Set a PK nail flush with the surface of the highway.

from which

An iron post, 2 1/2 ins. diam., set in concrete 6" below the surface of the ground and 4 lks. N. of a right-of-way fence, with standard Utah State Highway brass cap, bears N. $0^{\circ} 55'$ W., 75.8 lks. (50 ft) dist.

An iron post, 2 1/2 ins. diam., set in concrete, flush with the ground, bears, S. $0^{\circ} 55'$ E., 75.8 lks. (50 ft.) dist.

S. $89^{\circ} 09'$ W., bet. secs. 30 and 31.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 N., R. 13 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Along the centerline of Utah State Highway No. 30.

39.66

Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; falls in center of road, there is no remaining evidence of the original cor.

Set a railroad spike flush with the surface of the highway.

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears N. 44° 09' E., 1.071 chs. dist., with aluminum cap mkd. RM T13N R13W 1/4 S30 70.7 FT. 1989 and an arrow pointing to the cor.

Raise a mound of stone N. of the aluminum post.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears N. 45° 51' W. 1.071 chs. dist., with aluminum cap, mkd. RM T13N R13W 1/4 S30 70.7 FT. 1989 and an arrow pointing to the cor.

Raise a mound of stone N. of the aluminum post.

79.52

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivision of Section 31,
T. 13 N., R. 13 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam. firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the official record of the 1983 resurvey, executed by F.C. Profaizer.

N. 0° 40' W., on the N.-S. center line of sec. 31.

39.90

Point for the center 1/4 sec. cor. at intersection with the E - W. centerline

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap, mkd.

T13N R13W
C1/4 S31
1989

Set a cedar post alongside aluminum post.

79.81

The 1/4 sec. cor. of secs. 30 and 31.

**SURVEY OF THE SUBDIVISION OF SECTION 31,
T. 13 N., R. 13 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the 1/4 sec. cor. of secs. 31 and 32

S. $89^{\circ} 17' W.$, on the E. and W. center line of sec. 31

39.83

The center 1/4 sec. cor.

79.76

The 1/4 sec. cor. of secs. 31 and 36 on the W. bdy. of the Tp., hereinbefore described.

Survey of Tract 37,
T. 13 N., R. 13 W., Salt Lake Meridian, Utah

Beginning at cor. 1, tract 37.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T13N R13W
S31
1
TR37
1989

Corner falls 1 lk. W. of fence cor. projecting S. and W.

S. $89^{\circ} 26' W.$ along line 1-2, tract 37.

11.00

Point for cor. 2 of tract 37, on the W. bdy. of the Tp.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

R14W →

T13N
R14S R13W
S36 | S 31
2
TR37
1989

Cor. is located 2 lks. W. of N.-S. fence

Raised a mound of stone W. of aluminum post.

S. $0^{\circ} 34' E.$, along line 2-3, identical with the W. bdy. of the Tp.

10.00

Point for cor. 3, tract 37, on the W. bdy. of the Tp.

**SURVEY OF TRACT 37,
T. 13 N., R. 13 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

R14W →

T13N	
R14S	R13W
S36	TR37
	3
	S31
	1989

Cor. is located 2 lks. W. of N.-S. fence

Raised a mound of stone W. of aluminum post.

N. 89° 26' E., along line 3-4 of tract 37.

11.00

Point for cor. 4, tract 37

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T13N R13W	
TR37	
4	S31
1989	

Cor. is located 1 lk. W. of fence cor. projecting N. and W.

N. 0° 34' W. along line 4-1 of tract 37.

10.00

Cor. 1, of tract 37, hereinbefore described.

General Description

The area surveyed and resurveyed in T.13 N., R.13 W., is rolling low lands. The elevation ranges from about 5,400 to 5,600 ft. above sea level. The soil is mainly rocky loam. The vegetation consists of sagebrush and sparse native grasses. There is scattered stands of Juniper. Utah State Highway No. 30 runs along the N. bdy. of sec. 31. A landfill is located within tract 37.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Larry V. Judd	Land Surveyor
Gregg C. Ostergaard	Surveying Technician

CERTIFICATE OF SURVEY

I, *Richard A. Zaninovich, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *4th day of November, 1988*, I have *dependently resurveyed a portion of the west boundary and a portion of the subdivisional lines and surveyed the subdivision of section 31 and Tract 37, in Township 13 North, Range 13 West*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 7, 1989

Date


(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines and the survey of the subdivision of section 31 and Tract 37, Township 13 North, Range 13 West, Salt Lake Meridian, Utah*,

executed by *Richard A. Zaninovich, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

December 11, 1989

Date


(Acting Chief Cadastral Surveyor, Utah State Office)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

ORIGINAL
OF
THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE NORTH BOUNDARY

THE EAST BOUNDARY,

AND A PORTION OF THE SECTION LINES

AND A PARTIAL SUBDIVISIONAL SURVEY

OF

SECTIONS 1, 11, 13, 14, 23, 24, 25, 26, AND 35

IN

TOWNSHIP 29 SOUTH, RANGE 7 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Gail E. Reynolds
Cadastral Surveyor

Under special instructions dated *January 20, 1988*, approved *February 18, 1988*, which provided for the surveys included under Group Number 723, and assignment instructions dated *February 29, 1988*.

Survey commenced *March 4, 1988*

Survey completed *June 1, 1988*

INDEX DIAGRAM

Township 29 South, Range 7 West

					14
6	5	4	3	2 29	1 12
					28
7	8	9	10	11 27	12 10
				35	26
18	17	16	15	14 25	13 9
				35	24
19	20	21	22 34	23 23	24 8
				33	23
30	29	28	27 32	26 22	25 7
				31	20
31	32	33	34 30	35 19	36 6
				5	2

Old Fort Cameron Military Boundary - Page 15
 Subdivision of Section 1 - Page 36
 Subdivision of Section 11 - Page 39
 Subdivision of Section 13 - Page 40
 Subdivision of Section 14 - Page 41
 Subdivision of Section 23 - Page 43
 Subdivision of Section 24 - Page 47
 Subdivision of Section 25 - Page 48
 Subdivision of Section 26 - Page 48
 Subdivision of Section 35 - Page 51

TOWNSHIP 29 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary, a portion of the north boundary, the east boundary, a portion of the section lines and a partial subdivision of sections 1, 11, 13, 14, 23, 24, 25, 26, and 35, in T. 29 S., R. 7 W., Salt Lake Meridian, Utah.

History of Surveys

		<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>SOUTH BOUNDARY</u>					
All	J. Bausman	1870			
All			H. Fitzhugh	1882	
Portion			E.W. Koeber	1890	
Portion			Page and Swan	1897	
<u>EAST BOUNDARY</u>					
All	J. Bausman	1869			
Portion			E.W. Koeber	1890	
Portion			Page and Swan	1897	
<u>WEST BOUNDARY</u>					
All	J. Bausman	1869			
<u>NORTH BOUNDARY</u>					
Portion	J. Bausman	1870			
Portion	A.D. Ferron	1878	A.D. Ferron	1878	
Portion			Page and Swan	1897	
<u>SUBDIVISION</u>					
Portion	J. Bausman	1869			
Portion	E.W. Koeber	1890	E.W. Koeber	1890	
Portion	Page and Swan	1897	Page and Swan	1897	
<u>FORT CAMERON MILITARY RESERVATION</u>					
Portion	W.A. Jones	1872			
Portion	H. Douglas	1876			
All			E.W. Koeber	1890	
<u>FORT CAMERON WOOD AND TIMBER RESERVATION</u>					
All	C.E. Lloyd	1879			
All			E.W. Koeber	1890	

TOWNSHIP 29 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 723, Utah, dated January 20, 1988.

The directions of lines were determined by references to true meridians established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions. Lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic coordinates of the township cor. of Tps. 29 and 30 S., Rs. 6 and 7 W., as determined by ties made to U.S.G.S. supplemental horizontal control station CC 6SW/30S/7W, located on the W. bdy. of section 6, T. 30 S., R. 7 W., is as follows:

Latitude $38^{\circ} 14' 06.09''$ N. Longitude $112^{\circ} 34' 58.09''$ W.
N.A.D. 1927

The mean magnetic declination is: $15 \frac{1}{2}^{\circ}$ E.

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
J. Bausman, U.S. Deputy Surveyor in 1870,
the Resurvey Executed by H. Fitzhugh,
U.S. Deputy Surveyor in 1882, the Resurvey by
E.W. Koeber, U.S. Deputy Surveyor in 1890, and the Resurvey
Executed by Page and Swan, U.S. Deputy Surveyors in 1897)

Beginning at the cor. of Tps. 29 and 30 S., Rs. 6 and 7 W., monumented with a sandstone, 24x13x5 ins., firmly set 10 ins. in the ground and plainly mkd. 6 notches on N and S faces. Witnessed by a mound of stone to W, from which the original bearing tree

A juniper, 10 ins. diam., bears $S. 79 \frac{3}{4}^{\circ} W.$, 73 lks. dist.,
mkd. with definite scribe marks.

At the corner point

Set a stainless steel post, 30 ins. long, $2 \frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 29 S
R 7 W R 6 W
S 36 | S 31
S 1 | S 6
T 30 S
1988

Bury the mkd. stone alongside the stainless steel post.

From this cor., a lava rock, 18x8x6 ins., plainly mkd. 6 notches on N and S faces, firmly set in a fence cor., (four strand barbwire) bears N and W, bears S. $71^{\circ} 09' 46''$ W., 5.074 chs. dist. (unknown origin).

N. $89^{\circ} 47'$ W., bet. secs. 1 and 36.

Over rolling bench land, through pinon, juniper, sagebrush, and railed area.

20.47

The 1 1/2 mile post of the Old Fort Cameron Wood and Timber Reservation, monumented, with a trachyte stone, 20x12x10 ins., lying loose in a scattered mound of stone, plainly mkd. 1 groove on E face and 5 grooves on W face. This cor. will also function as the E 1/16 sec. cor. of secs. 1 and 36.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 29 S R 7 W
M P 1 1/2
F C W R
S 36
E 1/16 S 1
T 30 S
1988

Bury the mkd. stone alongside the stainless steel post.

This cor. is located in open railed area in sagebrush and native grasses.

N. $89^{\circ} 47'$ W., beginning new measurement.

Over rolling bench land, through railed area in sagebrush and native grasses.

19.95

The 1/4 sec. cor. of secs. 1 and 36, monumented with a sandstone, 20x12x10 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on N face. From which original bearing trees

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF

T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A juniper, 12 ins. diam., bears S. 63° W., 76 1/2 lks. dist.,
mkd. 1/4 BT. (record, S. $62\frac{3}{4}^{\circ}$ W., 77 lks.)

A juniper, 14 ins. diam., bears S. 83° W., 75 lks. dist.,
mkd. 1/4 BT. (record, 74 lks.)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
 $\frac{S\ 36}{S\ 1}$
 1/4 T 30 S
 1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of corner.

Cor. is located in E-W 4 strand barbwire fence line.

N. $89^{\circ} 07'$ W., beginning new measurement.

Over rolling bench land, through sagebrush and native grasses of railed area.

41.24

The cor. of secs. 1, 2, 35, and 36, monumented with a lava rock, 18x12x8 ins.,
firmly set 8 ins. in the ground and plainly mkd. 1 notch on E and 5 notches
on W edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground,
and in a collar of stone, with brass cap mkd.

T 29 S R 7W
 $\frac{S\ 35}{S\ 2} \mid \frac{S\ 36}{S\ 1}$
 T 30 S
 1988

Bury the mkd. stone alongside the stainless steel post.

Cor. is located on gently rolling land in sagebrush and native grasses.

S. $89^{\circ} 10'$ W., bet. secs. 2 and 35.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over rolling bench land, through sagebrush, native grasses and widely scattered juniper growth.

19.78 Point for the E 1/16 sec. cor. of secs. 2 and 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
 S 35
 E 1/16 S 2
 T 30 S
 1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of corner.

39.56 The 1/4 sec. cor. of secs. 2 and 35, monumented with a lava rock, 17x12x8 ins., firmly set in a mound of stone and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
 S 35
 1/4 S 2
 T 30 S
 1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 1 ft. high, N of corner.

Cor. is located on nearly level bench land in sagebrush, native grasses and widely scattered juniper growth.

N. 89° 49' W., beginning new measurement.

20.10 Point for the W 1/16 sec. cor. of secs. 2 and 35 (not monumented).

40.20 The cor. of secs. 2, 3, 34, and 35, monumented with a netwire fence cor., bears N and W. This point is agreeable with local landowner and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

T 29 S R 7 W
 $\frac{S\ 34}{S\ 3} \mid \frac{S\ 35}{S\ 2}$
 T 30 S
 1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

Cor. is located in bottom land of South Creek.

From this cor., the closing cor. of secs. 6 and 7, T. 30 S., R. 7 W., (U.S.G.S. Supplementary Horizontal Control Station CC 6SW/30S/7W), bears S. $76^{\circ} 05.1'$ W., 334.432 chs. dist.

Dependent Resurvey of the East Boundary,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
J. Bausman, Deputy Surveyor in 1869, the Resurvey Executed
by E.W. Koeber, Deputy Surveyor in 1890 and the Resurvey
Executed by Page and Swan, Deputy Surveyors in 1897)

From the cor. of Tps. 29 and 30 S., Rs. 6 and 7 W., hereinbefore described.

N. $0^{\circ} 13'$ E., bet. secs. 31 and 36.

Over rolling bench land, through sagebrush, native grasses, juniper, and pinon growth.

40.38

The 1/4 sec. cor. of secs. 31 and 36, monumented with a limestone, 19x8x7 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
 R 7 W R 6 W
 $\frac{1}{4}$
 $\frac{S\ 36}{S\ 31}$
 1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ} 08'$ E., beginning new measurement.

40.40

The cor. of secs. 25, 30, 31, and 36, monumented with a trachyte stone, 20x13x12 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on N and 1 notch on S edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S	
R 7 W R 6 W	
S 25	S 30
S 36	S 31
1988	

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

From this cor., a lava rock, 18x12x12 ins., firmly set in netwire fence cor., bears S and W, plainly mkd. 5 notches on N and 1 notch on S edges, bears S. $63^{\circ} 36'$ W., 4.22 chs. dist. (unknown origin).

N. $3^{\circ} 49'$ W., bet. secs. 25 and 30.

Over rolling W slope, through pinon and juniper growth.

38.18

The 1/4 sec. cor. of secs. 25 and 30, and also the 14 1/2 mile post of the Old Fort Cameron Military Reservation, monumented with a trachyte stone, 18x12x12 ins., firmly set 10 ins. in the ground and plainly mkd. with OMR on E face, a 14 1/2M on W face, 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S	
R 7 W R 6 W	
1/4	
S 25	S 30
14 1/2 M-OMR	
1988	

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on rolling SW slope in pinon and juniper growth.

N. 0° 16' E., beginning new measurement.

40.86

Point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 29 S
R 7 W R 6 W
S 24 | S 19
S 25 | S 30
1988

Cor. is located on rolling W slope in pinon and juniper growth.

N. 0° 16' E., bet. secs. 19 and 24.

Over rolling W slope, through pinon and juniper growth.

40.86

Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
1/4
S 24 | S 19
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

81.72

The cor. of secs. 13, 18, 19, and 24, monumented with a wood survey stake in a mound of stone. This point is being used by local landowners and local surveyors and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone 4 ft. base, to top of brass cap, mkd.

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 29 S
R 7 W R 6 W
S 13 | S 18
S 24 | S 19
1988

Cor. is located on N slope in oakbrush, under E-W power line.

N. 3° 24' E., bet. secs. 13 and 18.

Over bottom land of Beaver River.

20.575 Point for the S 1/16 sec. cor. of secs. 13 and 18.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
S 1/16
S 13 | S 18
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located on nearly level bottom land in pasture.

41.15 The 1/4 sec. cor. of secs. 13 and 18, monumented with a trachyte stone, 16x8x8 ins., firmly set 8 ins. in the ground, and dimly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
1/4
S 13 | S 18
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

N. 0° 26' E., beginning new measurement.

Over rolling bench land, through sagebrush, pinon and juniper growth.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**40.27**

The cor. of secs. 7, 12, 13, and 18, and the 4 mile post of the Old Fort Cameron Military Reservation, monumented with a lava rock, 20x12x8 ins., firmly set 8 ins. in the ground and plainly mkd. 2 notches on N and 4 notches on S edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
MP 4
S 12 | S 7
S 13 | S 18
FCMR
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

N. 0° 23' E., bet. secs. 7 and 12.

Over rolling bench land, through sagebrush, pinon and juniper growth.

39.23

Point for the 1/4 sec. cor. of sec. 12 only.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
1/4 |
S 12 |
1988

40.44

The original 1/4 sec. cor. of secs. 7 and 12, monumented with a sandstone, 16x8x6 ins., firmly set in a mound of stone and plainly mkd. 1/4 on W face. This cor. will now function as an angle point.

At the corner point

**DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
A P
S 12 | S 7
1988

Bury the mkd. stone alongside the stainless steel post.

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located in bottom of draw, drains SW.

N. 0° 31' E., beginning new measurement.

0.47 Point for the 1/4 sec. cor. of sec. 7, T. 29 S., R. 6 W.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
| 1/4
| S 7
1988

38.70 The closing cor. of secs. 1 and 12, monumented with a cobblestone, 24x14x12 ins., firmly set in a mound of stone, and plainly mkd. 6 grooves on E and W faces, and 5 notches on S edge.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
C S 1 |
C S 12 | S 7
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, NE of cor.

Cor. is located 8 lks. S of draw, drains W.

**DEPENDENT RESURVEY OF THE EAST BOUNDARY OF]
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**40.38**

The cor. of secs. 6 and 7, T. 29 S., R. 6 W., monumented with a cobblestone, 18x6x6 ins., firmly set 8 ins. in the ground and plainly mkd. 1 notches on N and 5 notches on S edges, from which original bearing trees

A juniper stump, 16 ins. diam., bears S. $28\frac{3}{4}^{\circ}$ E.,
22 lks. dist.

A juniper, 18 ins. diam., bears N. 26° W., 32 lks. dist.,
mkd. with visible scribe marks on blaze.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground,
with brass cap mkd.

T 29 S
R 7 W R 6 W
| S 6
S 1 | S 7
1988

Bury the mkd. stone alongside the stainless steel post.

N. 0° 21' E., bet. secs. 1 and 6.

Over rolling bench land, through sagebrush, pinon and juniper growth.

18.50

Point for the S 1/16 sec. cor. of sec. 1 only.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
and in a collar of stone, with brass cap mkd.

T 29 S
R 7 W R 6 W
S 1/16 |
S 1 |
1988

20.18

Point for the S 1/16 sec. cor. of sec. 6 only, T. 29 S., R. 6 W.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground,
and in a collar of stone, with brass cap mkd.

T 29 S
R 7 W R 6 W
| S 1/16
| S 6
1988

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 29 S. R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

38.68

Point for the 1/4 sec. cor. of sec. 1 only.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
1/4 |
S 1 |
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

40.36

Point for the 1/4 sec. cor. of sec. 6 only, T. 29 S., R. 6 W., at proportionate measurement; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
| 1/4
| S 6
1988

Set a 5 ft. steel fence post alongside the stainless steel post.

Cor. is located on nearly level land in sagebrush and native grasses.

80.72

Point for the cor. of Tps. 28 and 29 S., Rs. 6 and 7 W., as established at record distance from its remaining bearing trees. The original cor., a cobblestone, 20x11x4 ins., plainly mkd. 6 notches on N and S edges was lying loose on ground.

A juniper, 8 ins. in diam., bears N. 74° E., 12 lks. dist.,
(record, N. 70° E.), mkd. T28S R6W S31 BT. This tree is the
fence cor., 4 strand barbwire, bears E and S.

A juniper stump, 10 ins. diam., bears N. 15 1/2° W., 75 lks. dist.,
(record, N. 14 1/2° W.).

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 28 S
R 7 W R 6 W
S 36 | S 31
S 1 | S 6
T 29 S
1988

Bury the mkd. stone alongside the stainless steel post.

Cor. is located on E side of trail road, bears NE and SW in juniper and
pinon growth.

Dependent Resurvey of a Portion of the North Boundary,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by J. Bausman,
Deputy Surveyor in 1870, Survey and Resurvey by
A.D. Ferron, Deputy Surveyor in 1878
Resurvey by Page and Swan, U.S. Deputy Surveyors in 1897)

S. 89° 02' W., bet. secs. 1 and 36.

Over rolling bench land, through pinon and juniper growth.

41.34 Point for the 1/4 sec. cor. of sec. 36, T. 28 S., R. 7 W., at proportionate dist.;
not monumented.

42.96 Point for the 1/4 sec. cor. of sec. 1 only, at proportionate measurement; there
is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 28 S R 7 W
1/4 S 1
T 29 S
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located in cultivated land.

62.83 Point for the W 1/16 sec. cor. of sec. 1 only, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

82.70

The cor. of secs. 1, 2, 35, and 36, monumented with a cobblestone, 17x6x5 ins., firmly set 7 ins. in the ground and plainly mkd. 1 notch on E and 5 notches on W edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 28 S R 7 W
S 35 | S 36
S 2 | S 1
T 29 S
1988

Bury the mkd. stone alongside the stainless steel post.

Cor. is located on nearly level cultivated land.

Dependent Resurvey of a Portion of the
the Old Fort Cameron Military Boundary,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey and Resurvey Executed by
E.W. Koeber, Deputy Surveyor in 1890, the Survey and Resurvey
Executed by Page and Swan, Deputy Surveyors in 1897)

From the 1/4 sec. cor. of secs. 25 and 30, also the 14 1/2 mile post of the Old Fort Cameron Military Reservation, hereinbefore described.

N. 89° 14' W., on the 15 mile line of the Old Fort Cameron Military Boundary through sec. 25.

Over rolling bench land, through pinon and juniper growth.

15.02

No evidence of the mile post 21 of the Old Fort Cameron Wood and Timber Reservation could be found.

20.28

Point for the Initial Point of the Old Fort Cameron Wood and Timber Reservation, at proportionate measurement; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE
OLD FORT CAMERON MILITARY BOUNDARY,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 29 S R 7 W

C	S 25		IP	C
			FCWTR	
			1988	

39.55

Point for the center 1/4 sec. cor. of sec. 25, S side only.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 29 S R 7 W	
	FCMR	
C	S 25	C
	C 1/4	
	1988	

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

Cor. is located on rolling bench land in juniper and pinon.

40.04

The mile post 15 of the Old Fort Cameron Military Reservation, also the center 1/4 sec. cor. of sec. 25, N. side only, monumented with a trachyte stone, 18x16x5 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 M 15 OMR on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 29 S R 7 W	
	MP 15	
	FCMR	
	C 1/4	
	S 25	
C		C
	1988	

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

N. 89° 44' W., beginning new measurement.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

DEPENDENT RESURVEY OF A PORTION OF THE
OLD FORT CAMERON MILITARY BOUNDARY,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.18 Point for the closing 1/4 sec. cor. of secs. 25 and 26, hereinafter described.

39.97 The mile post 15 1/2 and the 1/4 sec. cor. of secs. 25 and 26, on the Old Fort Cameron Military Reservation, monumented with a sandstone, 16x12x6 ins., firmly set 8 ins. in the ground and plainly mkd. 1/4 on W face and 1/2 MOMR on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
MP 15 1/2
FCMR
1/4
S 26 | S 25
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Bury the mkd. stone alongside the stainless steel post.

N. 87° 55' W., on the 15 mile line of the Old Fort Cameron Military Boundary through sec. 26.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

39.09 Point for the center 1/4 sec. cor. of sec. 26, S side only.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
FCMR
C S 26 C
C 1/4
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

Set a 6 ft. steel fence post alongside the stainless steel post.

**DEPENDENT RESURVEY OF A PORTION OF THE
OLD FORT CAMERON MILITARY BOUNDARY,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**39.67**

The mile post 16 of the Old Fort Cameron Military Reservation Boundary, also the center 1/4 sec. cor. of sec. 26, North side only, monumented with a trachyte stone, 16x15x8 ins., firmly set 8 ins. in the ground and plainly mkd. 1/4 M 16 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C 1/4 S26 MP 16
C C
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

N. 89° 49' W., on the 16 mile line of the Old Fort Cameron Military Boundary, through sec. 26.

Over rolling bench land, through sagebrush and native grasses.

19.555

Point for the center W 1/16 sec. cor. of sec. 26, S side only, not monumented.

20.10

Point for the center W 1/16 sec. cor. of sec. 26, N side only, not monumented.

39.69

The closing 1/4 sec. cor. of secs. 26 and 27, monumented with a trachyte stone, 18x8x8 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on S face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
S 27 | S 26
1/4
CC
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

**DEPENDENT RESURVEY OF A PORTION OF THE
OLD FORT CAMEROM MILITARY BOUNDARY,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**40.20**

The mile post 16 1/2 and the 1/4 sec. cor. of secs. 26 and 27, on the Old Fort Cameron Military Reservation Boundary, monumented with a trachyte stone, 16x14x10 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

OMR
T 29 S R 7 W
1/4
S 27 | S 26
1988

Bury the mkd. stone alongside the stainless steel post.

Cor. is located in a netwire fence cor., bears N, S and W.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 29 S., R. 7 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
J. Bausman, Deputy Surveyor in 1870, the Survey and
Resurvey by E.W. Koeber, Deputy Surveyors in 1890,
the Survey and Resurvey Executed by
Page and Swan, Deputy Surveyors in 1896)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 04' E., bet. secs. 35 and 36.

Over rolling bench land, through sagebrush and native grasses.

20.07

Point for the S 1/16 sec. cor. of secs. 35 and 36.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
S 1/16
S 35 | S 36
1988

Cor. is located in a netwire fence line, bears N and S.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.14

The 1/4 sec. cor. of secs. 35 and 36, monumented with a lava rock, 20x10x6 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
1/4
S 35 | S 36
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located in a netwire fence line, bears N and S.

N. 0° 01' W., beginning new measurement.

40.09

The cor. of secs. 25, 26, 35, and 36, monumented with a trachyte stone, 22x8x8 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on S and E edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
S 26 | S 25
S 35 | S 36
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located in a netwire fence cor., bears E and S.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.

N. 89° 32' W., bet. secs. 25 and 36.

Over rolling bench land, through sagebrush, pinon and juniper growth.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**21.88**

The 1/2 mile post on the Old Fort Cameron Wood and Timber Reservation Boundary, monumented with a trachyte stone, 20x10x10 ins., firmly set 10 ins. in the ground and plainly mkd. USR and 1 notch on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 29 S R 7 W
MP 1/2
FCWTR
S 25
S 36
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 89° 52' W., beginning new measurement.

19.865

The 1/4 sec. cor. of secs. 25 and 36, monumented with a sandstone, 18x10x8 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
S 25
1/4 S 36
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

From this cor., a lava rock, 18x12x8 ins., firmly set in a netwire fence line, bears E and W and plainly mkd. 1/4 on N face, bears S. 51° 31' W., 3.336 chs. dist. (unknown origin).

N. 89° 59' W., beginning new measurement.

Over rolling bench land, through sagebrush and native grasses.

40.11

The cor. of secs. 25, 26, 35, and 36.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 08' E., bet. secs. 25 and 26.

Over rolling bench land, through sagebrush, pinon and juniper growth.

- 38.57** Point for the closing 1/4 sec. cor. of secs. 25 and 26, at intersection with the Old Fort Cameron Military Boundary (E-W center line of sec. 25), hereinbefore described.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W	
FCMR	
S 26	S 25
C	C
1/4	
1988	

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

- 40.28** The original closing 1/4 sec. cor. of secs. 25 and 26, monumented with a sandstone, 14x10x10 ins., firmly set 8 ins. in the ground and plainly mkd. 1/4 on S face. I additionally mark the stone AM and buried 6 ins. below the surface of the ground.

From the 1/4 sec. cor. of secs. 25 and 26, also the mile post 15 1/2 of the Old Fort Cameron Military Reservation.

N. 0° 40' E., bet. secs. 25 and 26.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

- 42.50** The cor. of secs. 23, 24, 25, and 26, monumented with a quartzite stone, 24x16x12 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on E and 2 notches on S faces.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W	
S 23	S 24
S 26	S 25
1988	

Bury the mkd. stone alongside the stainless steel post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp.,
hereinbefore described.

N. $85^{\circ} 17'$ W., bet. secs. 24 and 25.

Over rolling bench land, through dense pinon and juniper growth.

39.59 The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, monumented with a lava rock, 12x12x12
ins., firmly set 6 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground
to bedrock, and in a collar of stone, with brass cap mkd.

T 29 S R 7 W
 S 24
 $\frac{1}{4}$ S 25
 1988

Bury the mkd. stone alongside the stainless steel post.

S. $88^{\circ} 42'$ W., beginning new measurement.

Over rolling bench land, through sagebrush, scattered pinon and juniper
growth.

40.25 The cor. of secs. 23, 24, 25, and 26.

N. $0^{\circ} 03'$ E., bet. secs. 23 and 24.

Over rolling bench land, through sagebrush, scattered pinon and juniper
growth.

20.075 Point for the S $\frac{1}{16}$ sec. cor. of secs. 23 and 24.

Set a stainless steel post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
 S $\frac{1}{16}$
 S 23 | S 24
 1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**40.15**

The 1/4 sec. cor. of secs. 23 and 24, monumented with a trachyte stone,
12x10x6 ins., firmly set 6 ins. in the ground and plainly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground,
and in a collar of stone, with brass cap mkd.

T 29 S R 7 W
1/4
S 23 | S 24
1988

Bury the mkd. stone alongside the stainless steel post.

Cor. is located in a 4 strand barbwire fence line, bears E-W and N.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.,
hereinbefore described.

N. 89° 51' W., bet. secs. 13 and 24.

Over bottom land, through oak, cottonwoods, pinon, juniper and residential
area.

20.005 Point for the E 1/16 sec. cor. of secs. 13 and 24.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
S 13
E 1/16 S 24
1988

Cor. is located 2.7 lks. S of 4 strand barbwire fence line, bears E and W,
under power line, bears E and W.

40.01

Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there
is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
S 13
1/4 S 24
1988

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. falls 4 1/2 lks. N of E-W power line in residential area.

80.02

The cor. of secs. 13, 14, 23, and 24, monumented with a 2 in. iron pipe, with a brass cap, mkd. with a cross (X) (unknown origin), set in concrete, is being used by local landowners, and local surveyors, and is accepted as a careful and faithful perpetuation of the position of the original corner. Pipe in poor condition.

At the corner point

Set a 1 in. iron post, 15 ins. long, inside old pipe, 4 ins. below surface of the ground, with brass cap mkd.

T 29 S R 7 W	
S 14	S 13
S 23	S 24
1988	

Cor. is located on E edge of Utah State Highway 153, bears N and S and 6.6 lks. W of wood fence cor., bears E and S.

N. 0° 12' E., bet. secs. 13 and 14.

Over residential area.

20.00

Point for the S 1/16 sec. cor. of secs. 13 and 14.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W	
S 1/16	
S 14	S 13
1988	

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located 29 lks. N of canal, 6 ins. deep, 10 lks. wide, drains W.

40.00

The 1/4 sec. cor. of secs. 13 and 14, monumented with a trachyte stone, 10x8x5 ins., and a trachyte stone, 18x12x5 ins., firmly set in a mound of stone and plainly mkd. 1/4 on W faces.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 29 S R 7 W
1/4
S 14 | S 13
1988

Bury the mkd. stones alongside the stainless steel post.

N. 0° 12' E., beginning new measurement.

Over rolling bench land, through sagebrush and native grasses.

40.07

The cor. of secs. 11, 12, 13, and 14, and also the 3 mile post of the Old Fort Cameron Military Reservation, monumented with a sandstone, 14x8x6 ins., firmly set 6 ins. in the ground and plainly mkd. 1 notch on E and 4 notches on S faces and 3 M on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
S 11 | S 12
S 14 | S 13
3M-OMR
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.

S. 88° 13' W., bet. secs. 12 and 13, along Old Fort Cameron Military Reservation Boundary.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

42.62

Point for the 1/4 sec. cor. of sec. 12 only.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T 29 S R 7 W

1/4 S 12

FCMR

1988

43.13

The 1/4 sec. cor. of sec. 13 only, and also the 3 1/2 mile post of the Old Fort Cameron Military Reservation Boundary, monumented with a lava rock, 12x10x6 ins., firmly set 6 ins. in the ground and plainly mkd. 3 1/2 M on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W

MP 3 1/2

1/4 S 13

FCMR

1988

Bury the mkd. stone alongside the stainless steel post.

Set a 6 ft. steel fence post alongside the stainless steel post.

N. 89° 36' W., beginning new measurement.

39.38

The cor. of secs. 11, 12, 13, and 14.

N. 0° 28' E., bet. secs. 11 and 12.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

40.97

The 1/4 sec. cor. of secs. 11 and 12, monumented with a limestone, 20x12x10 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W

1/4

S 11 | S 12

1988

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. $0^{\circ} 03'$ E., beginning new measurement.

40.12

The cor. of secs. 1, 2, 11, and 12, monumented with a 1/2 in. rebar in a mound of stone, used by local landowners and local surveyors and is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W			
<u>S 2</u>		<u>S 1</u>	
S 11		S 12	
1988			

S. $89^{\circ} 35'$ E., bet. secs. 1 and 12.

Over rolling bench land, through sagebrush, pinon and juniper growth.

19.575

Point for the W 1/16 sec. cor. of secs. 1 and 12.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 29 S R 7 W			
		<u>S 1</u>	
W 1/16		S 12	
1988			

39.15

The 1/4 sec. cor. of secs. 1 and 12, monumented with a limestone, 18x10x6 ins., firmly set 8 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W			
		<u>S 1</u>	
1/4		S 12	
1988			

Bury the mkd. stone alongside the stainless steel post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of cor.

Cor. is located on nearly level land in sagebrush, scattered pinon and juniper growth.

S. 89° 13' E., beginning new measurement.

43.56

The closing cor. of secs. 1 and 12, hereinbefore described.

From the cor. of secs. 1, 2, 11, and 12.

N. 0° 22' E., bet. secs. 1 and 2.

Over rolling pasture and cultivated land.

20.175

Point for the S 1/16 sec. cor. of secs. 1 and 2.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
S 1/16
S 2 | S 1
1988

Cor. is located under metal gate, bears E and W., 24 lks. W of fence cor., bears E-W and N and 7 lks. E of fence cor., bears E-S and W.

40.35

The 1/4 sec. cor. of secs. 1 and 2, monumented with a fence cor., bears N and W, and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
1/4
S 2 | S 1
1988

Cor. is located in pasture land.

N. 0° 21' E., beginning new measurement.

20.11

Point for the N 1/16 sec. cor. of secs. 1 and 2, not monumented.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

39.79 The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 21' W., bet. secs. 34 and 35.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

20.295 Point for the S 1/16 sec. cor. of secs. 34 and 35, not monumented.

40.59 The 1/4 sec. cor. of secs. 34 and 35, monumented with a trachyte stone, 18x10x8 ins., firmly set 6 ins. in the ground and plainly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
1/4
S 34 | S 35
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located in E-W fence line.

N. 0° 04' W., beginning new measurement.

20.08 Point for the N 1/16 sec. cor. of secs. 34 and 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
N 1/16
S 34 | S 35
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located in cultivated land.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**40.16**

The cor. of secs. 26, 27, 34, and 35, determined by cor. of fences bearing E and S, and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W			
S 27		S 26	
S 34		S 35	
1988			

Cor. is located in cultivated land.

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 57' W., bet. secs. 26 and 35.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

40.02

The 1/4 sec. cor. of secs. 26 and 35, monumented with a trachyte stone, 18x10x6 ins., firmly set 6 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W	
S 26	
1/4	S 35
1988	

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

N. 89° 56' W., beginning new measurement.

20.03

Point for the W 1/16 sec. cor. of secs. 26 and 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

T 29 S R 7 W
 S 26
 W 1/16 S 35
 1988

Cor. is located 4 lks. W of fence cor., bears S and W.

40.06 The cor. of secs. 26, 27, 34, and 35.

N. 0° 03' E., bet. secs. 26 and 27.

Over rolling bench land, through sagebrush.

19.99 Point for the S 1/16 sec. cor. of secs. 26 and 27, at proportionate distance;
not monumented.

40.07 The closing 1/4 sec. cor. of secs. 26 and 27, on the 16 mile line of the
Old Fort Cameron Military Reservation.

From the 1/4 sec. cor. of secs. 26 and 27.

N. 0° 05' E., on the 16 mile line of the Old Fort Cameron Military
Reservation Boundary, bet. secs. 26 and 27.

20.105 Point for the N 1/16 sec. cor. of secs. 26 and 27, not monumented.

40.21 The cor. of secs. 22, 23, 26, and 27 (also the initial point for the Old Fort
Cameron Military Boundary), monumented with a trachyte stone, 16x8x4 ins.,
firmly set in concrete and plainly mkd. 2 notches on E and S edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
 IPMR
 S 22 | S 23
 S 27 | S 26
 1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located in fence cor., bears N-S and W.

From the cor. of secs. 23, 24, 25, and 26.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. $89^{\circ} 12'$ W., bet. secs. 23 and 26.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

20.10 Point for the E 1/16 sec. cor. of secs. 23 and 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

	T 29 S R 7 W
	<u>S 23</u>
E 1/16	S 26
	1988

40.20 The 1/4 sec. cor. of secs. 23 and 26, monumented with a lava rock, 15x12x10 ins., firmly set 6 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.

	T 29 S R 7 W
	<u>S 23</u>
1/4	S 26
	1988

Bury the mkd. stone alongside the stainless steel post.

S. $89^{\circ} 48'$ W., beginning new measurement.

20.035 Point for the W 1/16 sec. cor. of secs. 23 and 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 29 S R 7 W
	<u>S 23</u>
W 1/16	S 26
	1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located 46 lks. W of N-S fence line.

40.07 The cor. of secs. 22, 23, 26, and 27.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 01' E., bet. secs. 22 and 23 (Old Fort Cameron Military Boundary).

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

20.16 Point for the S 1/16 sec. cor. of secs. 22 and 23, not monumented.

40.32 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; the only evidence of the original cor. was a concrete block, 24x8x8 ins., mkd. 1/4 SE M, lying loose on the ground. This is also the 1/2 mile post of the Old Fort Cameron Military Boundary.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
MP 1/2
1/4
S 22 | S 23
1988

Deposit the concrete block alongside the stainless steel post.

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located on the E side of graveled road, bears N and S.

Over pasture land and residential area.

80.64 The cor. of secs. 14, 15, 22, and 23, monumented with a 1/2 in. aluminum pipe, 8 ft. long, located in a fence cor., bears N-S and W, used by local surveyors and is accepted as a careful and faithful perpetuation of the position of the original cor. Also the mile post 1 of FCMR.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
MP 1
S 15 | S 14
S 22 | S 23
1988

Cor. is located on W side of paved road, bears N and S.

From the cor. of secs. 13, 14, 23, and 24.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. $89^{\circ} 59'$ W., bet. secs. 14 and 23.

Over residential area.

19.93 Point for the E 1/16 sec. cor. of secs. 14 and 23, not monumented.

39.86 The 1/4 sec. cor. of secs. 14 and 23, monumented with a trachyte stone, 18x14x8 ins., firmly set in concrete and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W

S 14

1/4 S 23

1988

Bury the mkd. stone alongside the stainless steel post.

Cor. is located in fence cor., bears N-S and W.

From the cor. of secs. 11, 12, 13, and 14, also Mile Post 3 of the Old Fort Cameron Military Reservation.

N. $89^{\circ} 21'$ W., bet. secs. 11 and 14.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

20.06 Point for the E 1/16 sec. cor. of secs. 11 and 14.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W

S 11

E 1/16 S 14

1988

40.12 The 1/4 sec. cor. of secs. 11 and 14, also the mile post 2 1/2 of FCMR, monumented with a trachyte stone, 14x10x8 ins., firmly set 6 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
S 11
1/4 S 14
1988

Bury the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Survey of the Subdivision of Section 1,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 1 and 12.

N. 0° 46' E., on the N and S center line of sec. 1.

Over rolling bench land, through sagebrush, pinon and juniper growth.

20.59 Point for the center S 1/16 sec. cor. of sec. 1.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C
S 1/16 | S 1
C
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

40.225 Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E and W center line of sec. 1.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C 1/4 S 1
1988

Set a 6 ft. steel post alongside the stainless steel post.

60.77 Point for the center N 1/16 sec. cor. of sec. 1.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground,
and in a collar of stone, with brass cap mkd.

T 29 S R 7 W
C
N 1/16 | S 1
C
1988

81.10 The 1/4 sec. cor. of secs. 1 only, on the N. bdy. of the Tp., hereinbefore
described.

From the 1/4 sec. cor. of sec. 1 only, on the E. bdy. of the Tp., hereinbefore
described.

N. 89° 23' W., on the E and W center line of sec. 1.

Over rolling bench land, through sagebrush, scattered pinon and juniper
growth.

43.25 The center 1/4 sec. cor. of sec. 1.

62.97 Point for the center W 1/16 sec. cor. of sec. 1.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
W 1/16
C S 1 C
1988

Cor. is located on E edge of dirt road, bears NE and SW.

82.69 The 1/4 sec. cor. of secs. 1 and 2.

From the W 1/16 sec. cor. of secs. 1 and 12.

N. 0° 34' E., on the N and S center line of the SW 1/4 of sec. 1.

20.385 Point for the SW 1/16 sec. cor. of sec. 1, at intersection with the E and W
center line of the SW 1/4 of sec. 1.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

SURVEY OF THE SUBDIVISION OF SECTION 1,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 29 S R 7 W
SW 1/16 S 1
1988

Cor. is located under E and W fence line, 1.077 chs. W of fence cor., bears N and W (private surveyors' SW 1/16 sec. cor. of sec. 1 was established using improper procedures and is not utilized in the course of this survey).

40.29 The center W 1/16 sec. cor. of sec. 1.

From the center S 1/16 sec. cor. of sec. 1.

S. $89^{\circ} 49'$ W., on the E and W center line of the SW 1/4 of sec. 1.

19.65 The SW 1/16 sec. cor. of sec. 1.

39.30 The S 1/16 sec. cor. of secs. 1 and 2.

From the center W 1/16 sec. cor. of sec. 1.

N. $0^{\circ} 34'$ E., on the N and S center line of the NW 1/4 of sec. 1.

20.33 Point for the NW 1/16 sec. cor. of sec. 1, at intersection with the E and W center line of the NW 1/4 of sec. 1.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
NW 1/16 S 1
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located in cultivated land.

40.33 Point for the W 1/16 sec. cor. of sec. 1 only, on the N. bdy. of the Tp., hereinbefore described.

From the center N 1/16 sec. cor. of sec. 1.

S. $89^{\circ} 58'$ W., on the E and W center line of the NW 1/4 of sec. 1.

19.79 The NW 1/16 sec. cor. of sec. 1.

39.58 The point for the N 1/16 sec. cor. of secs. 1 and 2.

**SURVEY OF THE SUBDIVISION OF SECTION 11,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Survey of the Subdivision of Section 11,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 11 and 14.

N. $0^{\circ} 12'$ E., on the N and S center line of sec. 11.

Over rolling pasture land and cultivated land.

40.58 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E and W center line of sec. 11, point falls in an irrigation ditch, bears N and S and not monumented.

80.77 The 1/4 sec. cor. of secs. 2 and 11, monumented with a cobblestone, 14x8x7 ins., firmly set 6 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
 S 2
 1/4 S 11
 1988

Cor. is located in E and W fence line.

From the 1/4 sec. cor. of secs. 11 and 12.

N. $89^{\circ} 54'$ W., on the E and W center line of sec. 11.

20.15 Point for the center E 1/16 sec. cor. of sec. 11.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
 E 1/16
 C S 11 C
 1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located in cultivated land.

40.30 The point for the center 1/4 sec. cor. of sec. 1.

SURVEY OF THE SUBDIVISION OF SECTION 11,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

80.50

The 1/4 sec. cor. of secs. 10 and 11, monumented with a fence cor., bears E, W, and S. This point is being used by local landowners and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W

1/4

S 10 | S 11

1988

Cor. is located in cultivated land.

From the E 1/16 sec. cor. of secs. 11 and 14.

N. 0° 20 E., on the N and S center line of the SE 1/4 of sec. 11.

40.78

The E 1/16 sec. cor. of sec. 11.

Survey of the Subdivision of Section 13,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 13 and 24.

N. 0° 15' W., on the N and S center line of sec. 13.

20.26

Point for the center S 1/16 sec. cor. of sec. 13.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 5 1/2 ft. base, to top of brass cap, mkd.

T 29 S R 7 W

C

S 1/16 | S 13

C

1988

Cor. is located 6 lks. S of power line, bears E and W.

40.52

Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E and W center line of sec. 13.

**SURVEY OF THE SUBDIVISION OF SECTION 13,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 29 S R 7 W
C 1/4 S 13
1988

79.89

The 1/4 sec. cor. of sec. 13 only.

From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 24' W., on the E and W center line of sec. 13.

42.63

The center 1/4 sec. cor. of sec. 13.

82.33

The 1/4 sec. cor. of secs. 13 and 14.

From the S 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 46' W., on the E and W center line of the SE 1/4 of sec. 13.

41.32

The center S 1/16 sec. cor. of sec. 13.

S. 89° 46' W., on the E and W center line of the SW 1/4 of sec. 13.

39.85

The S 1/16 sec. cor. of secs. 13 and 14.

Survey of the Subdivision of Section 14,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 14 and 23.

N. 0° 01' E., on the N and S center line of sec. 14.

Over rolling bench land, through sagebrush.

20.135

Point for the center S 1/16 sec. cor. of sec. 14, not monumented.

40.27

Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E and W center line of sec. 14.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 29 S R 7 W
C 1/4 S 14
1988

Cor. is located 25 lks. N of canal, drains SW.

80.54 The 1/4 sec. cor. of secs. 11 and 14, and Mile Post 2 1/2 of Old Fort
Cameron Military Reservation.

From the 1/4 sec. cor. of secs. 13 and 14.

N. 89° 38' W., on the E and W center line of sec. 14.

19.995 Point for the center E 1/16 sec. cor. of sec. 14.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
E 1/16
C S 14 C
1988

Cor. is located 51 lks. E of a N-S fence line.

39.99 The center 1/4 sec. cor. of sec. 14.

80.49 The 1/4 sec. cor. of secs. 14 and 15, also the 1 1/2 mile post on the Old Fort
Cameron Military Reservation, determined by cor. of fences bearing N, E, S,
and W. This point is being used by local landowners and is accepted as the
best available evidence of the position of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
1/4
S 15 | S 14
1988

From the center E 1/16 sec. cor. of sec. 14.

N. 0° 07' E., on the N and S center line of the NE 1/4 of sec. 14.

**SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**40.17**

The E 1/16 sec. cor. of secs. 11 and 14.

From the point for the E 1/16 sec. cor. of secs. 14 and 23.

N. $0^{\circ} 06'$ E., on the N and S center line of the SE 1/4 of sec. 14.

20.065

Point for the SE 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the SE 1/4 of sec. 14.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
SE 1/16 S 14
1988

40.13

The center E 1/16 sec. cor. of sec. 14.

From the S 1/16 sec. cor. of secs. 13 and 14.

N. $89^{\circ} 50'$ W., on the E and W center line of the SE 1/4 of sec. 14.

19.96

The SE 1/16 sec. cor. of sec. 14.

39.92

Point for the center S 1/16 sec. cor. of sec. 14.

Survey of the Subdivision of Section 23,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 23 and 26.

N. $0^{\circ} 15'$ E., on the N and S center line of sec. 23.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

20.22

Point for the center S 1/16 sec. cor. of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C
S 1/16 | S 23
C
1988

**SURVEY OF THE SUBDIVISION OF SECTION 23,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

35.385 Point for the center north-north-south 1/256 sec. cor. of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C-N-N-S 1/256 S 23
1988

Cor. is located 2 lks. N and 5 lks. W of a fence cor., bears E and S.

40.44 Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E - W center line of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C 1/4 S 23
1988

Cor. is located 2 lks. N of fence cor., bears E and S in residential area.

80.13 The 1/4 sec. cor. of secs. 14 and 23.

From the 1/4 sec. cor. of secs. 23 and 24.

S. 89° 37' W., on the E - W center line of sec. 23.

Over rolling bench land, through sagebrush, pinon and juniper growth.

20.02 Point for the center E 1/16 sec. cor. of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
E 1/16
C S 23 C
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Cor. is located 23 lks. N of E - W fence line.

SURVEY OF THE SUBDIVISION OF SECTION 23,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

35.035

Point for the center west-west-east 1/256 sec. cor. of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C-W-W-E 1/256 S 23
1988

Cor. is located in fence cor., bears E, S and W.

40.04

The center 1/4 sec. cor. of sec. 23.

60.16

Point for the center W 1/16 sec. cor. of sec. 23, not monumented.

80.28

The 1/4 sec. cor. of secs. 22 and 23, and Mile Post 1/2 on the Old Fort Cameron Military Reservation.

From the E 1/16 sec. cor. of secs. 23 and 26.

N. 0° 09' E., on the N and S center line of the SE 1/4 of sec. 23.

20.15

Point for the SE 1/16 sec. cor. of sec. 23, at intersection with the E - W center line of the SE 1/4 of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
SE 1/16 S 23
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

40.30

The center E 1/16 sec. cor. of sec. 23.

From the S 1/16 sec. cor. of secs. 23 and 24.

S. 89° 24' W., on the E - W center line of the SE 1/4 of sec. 23.

20.06

The SE 1/16 sec. cor. of sec. 23.

40.12

The center S 1/16 sec. cor. of sec. 23.

From the center north-north-south 1/256 sec. cor. of sec. 23.

SURVEY OF THE SUBDIVISION OF SECTION 23,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $89^{\circ} 34'$ E., (mean bearing), on the E - W center line of the NW 1/4 of the NW 1/4 of the SE 1/4 of sec. 23.

5.01

Point for the northwest-northwest-southeast 1/256 sec. cor. of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
NW-NW-SE-1/256 S 23
1988

Cor. is located in fence line, bears E - W, 4 lks. W of fence cor., bears N and W.

N. $0^{\circ} 14'$ E., (mean bearing), on the N and S center line of the NW 1/4 of the NW 1/4 of the SE 1/4 of sec. 23.

5.05

The center-west-west-east 1/256 sec. cor. of sec. 23.

From the W 1/16 sec. cor. of secs. 23 and 26.

N. $0^{\circ} 08'$ E., on the N and S center line of the SW 1/4 of sec. 23.

20.19

Point for the SW 1/16 sec. cor. of sec. 23, at intersection with the E - W center line of the SW 1/4 of sec. 23.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
SW 1/16 S 23
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located 7 lks. N of fence line, bearings W and E, 25 lks., thence S.

40.38

The point for the center W 1/16 sec. cor. of sec. 23.

From the center S 1/16 sec. cor. of sec. 23.

S. $89^{\circ} 42'$ W., on the E - W center line of the SW 1/4 of sec. 23.

20.08

The SW 1/16 sec. cor. of sec. 23.

40.16

The point for the S 1/16 sec. cor. of secs. 22 and 23.

**SURVEY OF THE SUBDIVISION OF SECTION 24,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Survey of the Subdivision of Section 24,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 24 and 25.

N. $0^{\circ} 08'$ W., on the N and S center line of sec. 24.

Over rolling bench land, through sagebrush, pinon and juniper growth.

38.42 Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E - W center line of sec. 24.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C 1/4 S 24
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Cor. is located in E - W fence line.

78.57 The 1/4 sec. cor. of secs. 13 and 14.

From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., hereinbefore described.

N. $88^{\circ} 50'$ W., on the E - W center line of sec. 24.

Over rolling bench land, through sagebrush, pinon and juniper growth.

19.87 Point for the center E 1/16 sec. cor. of sec. 24.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
E 1/16
C S 24 C
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Cor. is located 7 lks. N of E - W fence line.

39.74 The center 1/4 sec. cor. of sec. 24.

**SURVEY OF THE SUBDIVISION OF SECTION 24,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**79.86**

The 1/4 sec. cor. of secs. 23 and 24.

From the center E 1/16 sec. cor. of sec. 24.

N. 0° 04' E., on the N and S center line of the NE 1/4 of sec. 24.

40.51

The E 1/16 sec. cor. of secs. 13 and 24.

Survey of the Subdivision of Section 25,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 25 and 36.

N. 0° 31' W., on the N and S center line of sec. 25.

Over rolling bench land, through sagebrush, pinon and juniper growth.

38.39

The center 1/4 sec. cor. of sec. 25 (south 1/2 only), on the Old Fort Cameron Military Reservation Boundary.

From the center 1/4 sec. cor. of sec. 25 (north 1/2 only), on the Old Fort Cameron Military Reservation Boundary.

N. 1° 00' E., on the N and S center line of sec. 25.

Over rolling bench land, through pinon and juniper growth.

43.60

The 1/4 sec. cor. of secs. 24 and 25.

From the 1/2 mile post on the Old Fort Cameron Wood and Timber Reservation Boundary, bet. secs. 25 and 36.

N. 1° 25' W., on the N and S center line of the SE 1/4 of sec. 25.

Over rolling bench land, through sagebrush, pinon and juniper growth.

38.20

The initial point for the Old Fort Cameron Wood and Timber Reservation on the Old Fort Cameron Military Reservation Boundary.

Survey of the Subdivision of Section 26,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 26 and 35.

N. 0° 21' E., on the N and S center line of sec. 26.

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

19.96

Point for the center S 1/16 sec. cor. of sec. 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C
S 1/16 | S 26
C
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

39.96

The center 1/4 sec. cor. of sec. 26 (south 1/2 only), on the Old Fort Cameron Military Reservation Boundary.

From the center 1/4 sec. cor. of sec. 26 (north 1/2 only), on the Old Fort Cameron Military Reservation Boundary.

N. 0° 06' W., on the N and S center line of sec. 26.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

20.245

Point for the center N 1/16 sec. cor. of sec. 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
C
N 1/16 | S 26
C
1988

40.49

The 1/4 sec. cor. of secs. 23 and 26.

From the W 1/16 sec. cor. of secs. 26 and 35.

N. 0° 12' E., on the N and S center line of the SW 1/4 of sec. 26.

19.97

Point for the SW 1/6 sec. cor. of sec. 26, at intersection with the E - W center line of the SW 1/4 of sec. 26.

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
SW 1/16 S 26
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

Cor. is located 2 lks. S of E - W fence line.

40.02 The point for the center W 1/16 sec. cor. of sec. 26 (south 1/2 only), on the Old Fort Cameron Military Reservation Boundary.

From the center S 1/16 sec. cor. of sec. 26.

N. 89° 54' W., on the E - W center line of the SW 1/4 of sec. 26.

20.08 The SW 1/16 sec. cor. of sec. 26.

40.16 The point for the S 1/16 sec. cor. of secs. 26 and 27.

From the point for the center W 1/16 sec. cor. of sec. 26 (north 1/2 only), on the Old Fort Cameron Military Reservation Boundary.

North, on the N and S center line of the NW 1/4 of sec. 26.

20.18 Point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E - W center line of the NW 1/4 of sec. 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
NW 1/16 S 26
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, NE of cor.

Set a 6 ft. steel fence post alongside the stainless steel post.

40.36 The W 1/16 sec. cor. of secs. 23 and 26.

From the center N 1/16 sec. cor. of sec. 26.

West, on the E - W center line of the NW 1/4 of sec. 26.

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

18.94 Netwire fence line, bears N and S.

20.07 The NW 1/16 sec. cor. of sec. 26.

40.14 The point for the N 1/16 sec. cor. of secs. 26 and 27.

Survey of the Subdivision of Section 35,
T. 29 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.,
hereinbefore described.

N. 0° 19' W., on the N and S center line of sec. 35.

Over rolling bench land, through sagebrush, scattered juniper and pinon
growth.

20.36 Point for the center S 1/16 sec. cor. of sec. 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
C
S 1/16 | S 35
C
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

40.72 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E - W
center line of sec. 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

T 29 S R 7 W
C 1/4 S 35
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

60.785 Point for the center N 1/16 sec. cor. of sec. 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground,
with brass cap mkd.

**SURVEY OF THE SUBDIVISION OF SECTION 35,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

T 29 S R 7 W
C
N 1/16 | S 35
C
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

80.85 The 1/4 sec. cor. of secs. 26 and 35.

From the 1/4 sec. cor. of secs. 35 and 36.

West, on the E - W center line of sec. 35.

Over rolling bench land, through sagebrush, scattered pinon and juniper growth.

19.905 Point for the center E 1/16 sec. cor. of sec. 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
E 1/16
C S 35 C
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

39.81 The center 1/4 sec. cor. of sec. 35.

59.925 Point for the center W 1/16 sec. cor. of sec. 35.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
W 1/16
C S 35 C
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

80.04 The 1/4 sec. cor. of secs. 34 and 35.

From the E 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described.

**SURVEY OF THE SUBDIVISION OF SECTION 35,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. $0^{\circ} 07'$ W., on the N and S center line of the SE $1/4$ of sec. 35.

20.215 Point for the SE $1/16$ sec. cor. of sec. 35, at intersection with the E - W center line of the SE $1/4$ of sec. 35.

Set a stainless steel post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
SE $1/16$ S 35
1988

Set a 6 ft. steel fence post alongside the stainless steel post.

40.43 The center E $1/16$ sec. cor. of sec. 35.

From the S $1/16$ sec. cor. of secs. 35 and 36.

S. $89^{\circ} 36'$ W., on the E - W center line of the SE $1/4$ of sec. 35.

19.845 The SE $1/16$ sec. cor. of sec. 35.

39.69 The center S $1/16$ sec. cor. of sec. 35.

From the point for the W $1/16$ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. $0^{\circ} 20'$ W., on the N and S center line of the SW $1/4$ of sec. 35.

20.325 Point for the SW $1/16$ sec. cor. of sec. 35, at intersection with the E - W center line of the SW $1/4$ of sec. 35.

Set a stainless steel post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 7 W
SW $1/16$ S 35
1988

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

40.65 The center W $1/16$ sec. cor. of sec. 35.

From the center S $1/16$ sec. cor. of sec. 35.

N. $89^{\circ} 54'$ W., on the E - W center line of the SW $1/4$ of sec. 35.

**SURVEY OF THE SUBDIVISION OF SECTION 35,
T. 29 S., R. 7 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 20.105** The SW 1/16 sec. cor. of sec. 35.
- 40.21** The point for the S 1/16 sec. cor. of secs. 34 and 35, not monumented.
From the center W 1/16 sec. cor. of sec. 35.
N. 0° 11' W., on the N and S center line of the NW 1/4 of sec. 35.
- 20.075** Point for the NW 1/16 sec. cor. of sec. 35, at intersection with the E - W center line of the NW 1/4 of sec. 35.
Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.
- T 29 S R 7 W
NW 1/4 S 35
1988
- Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.
- 40.15** The W 1/16 sec. cor. of secs. 26 and 35.
From the center N 1/16 sec. cor. of sec. 35.
N. 89° 58' W., on the E - W center line of the NW 1/4 of sec. 35.
- 20.07** The NW 1/4 sec. cor. of sec. 35.
- 40.14** The N 1/16 sec. cor. of secs. 34 and 35.

General Description

The land encompassed in this survey is located just east of the City of Beaver, Utah. The elevation is about 6200 ft. above sea level. The land is covered with sagebrush and groves of pinon and juniper. The land is used for livestock grazing and is a critical deer winter range.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ferrel D. Reynolds	Surveying Technician
Larry V. Judd	Cadastral Surveyor
Glen B. Hatch	Cadastral Surveyor
Ronald K. Baugh	Cadastral Surveyor
M. Ross Workman	Cadastral Surveyor

CERTIFICATE OF SURVEY

I, *Gail E. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *20th day of January, 1988*, I have *dependently resurveyed a portion of the south boundary, a portion of the north boundary, the east boundary, and a portion of the section lines and partially surveyed the subdivision of sections 1, 11, 13, 14, 23, 24, 25, 26, and 35, in Township 29 South, Range 7 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 27, 1989

Date

Gail E. Reynolds

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the south boundary, a portion of the north boundary, the east boundary and a portion of the section lines and a partial subdivisional survey of sections 1, 11, 13, 14, 23, 24, 25, 26, and 35, Township 29 South, Range 7 West, Salt Lake Meridian, Utah,*

executed by *Gail E. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

November 30, 1989

Date

Glen B. Hartsell

(Chief Cadastral Surveyor, Utah State Office)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
PORTIONS OF THE SOUTH BOUNDARY AND SUBDIVISIONAL LINES
AND THE
SURVEY OF THE SUBDIVISION OF SECTIONS 26 AND 34
IN
TOWNSHIP 39 SOUTH, RANGE 12 WEST

of the Salt Lake Meridian
In the State of Utah

EXECUTED BY

Richard A. Zaninovich
Cadastral Surveyor

Under special instructions dated *March 30, 1987*, approved *March 31, 1987*, which provided for the surveys included under Group Number 706, and assignment instructions dated *March 31, 1987*.

Survey commenced *June 22, 1987*

Survey completed *October 1, 1987*

INDEX DIAGRAM

Township 39 South, Range 12 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
				7	
30	29	28	27 6	26 5	25
			8	6	
31	32	33 8	34 5	35	36
	4	3	3	2	2

Subdivision of Section 26

- Page 9

Subdivision of Section 34

- Page 12

TOWNSHIP 39 SOUTH, RANGE 12 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes described the dependent resurvey of portions of the south boundary and subdivisional lines and the subdivisional survey of sections 26 and 34, in T. 39 S., R. 12 W., Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed bySOUTH BOUNDARY

All A. Nelson and W. Stumm 1911

SUBDIVISION

Portion	J. Gorlinski	1869
Portion	A. Nelson and W. Stumm	1911
Portion	A. Nelson and W. Stumm	1911

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 706, Utah dated March 30, 1987.

The directions of lines were determined by references to true meridians established on line by hour angle observations on the sun. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions. Lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 1 and 6, T. 40 S., Rs. 11 and 12 W., as determined from ties made to National Geodetic Survey Station "SPENDLOVE" and U.S.G.S. Triangulation Station "ANDERSON", is:

Latitude 37° 20' 39.77" N. Longitude 113° 08' 46.95 W.
N.A.D. 1927

The mean magnetic declination is 14 1/2° E.

Dependent Resurvey of a Portion of the South Boundary,
T. 39 S., R. 12 W., Salt Lake Meridian, Utah

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

(Reestablishment of the Survey Executed by
A. Nelson and W. Stumm, in 1911)

Beginning at the cor. of secs. 1 and 6 only, T. 40 S., Rs. 11 and 12 W., monumented with an iron post, 3 ins. diam., 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing trees

A cedar, 18 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ E., 33 lks. dist.,
mkd. T40S R11W S6 BT.

A pinon, 12 ins. diam., bears S. $64\frac{3}{4}^{\circ}$ W., 86 lks. dist.,
mkd. T40S R12W S1 BT. (record, 64 lks. dist.).

From this cor., National Geodetic Survey Station "SPENDLOVE, bears
S. $76^{\circ} 40.6'$ E., 171.14 chs. dist., monumented with a standard bronze disk.

N. $89^{\circ} 56'$ W., on the S. bdy. of sec. 36.

Over broken mountainous land, through pinon and juniper growth.

18.37 The $\frac{1}{4}$ sec. cor. of sec. 36 only, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which an original bearing tree

A pinon, 12 ins. diam., bears N. 40° E., 60 lks. dist.,
mkd. $\frac{1}{4}$ S 36 BT. (record, N. $12^{\circ} 30'$ E.).

West, beginning new measurement.

21.79 Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only, described in the concurrent resurvey of T. 40 S., R. 12 W.

39.98 The cor. of secs. 35 and 36 only, monumented with an iron post, 3 ins. diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey.

West, along the S. bdy. of sec. 35.

Over rolling mountainous land, through pinon and juniper growth.

21.97 The closing cor. of secs. 1 and 2, T. 40 S., R. 12 W., described in the concurrent resurvey of T. 40 S., R. 12 W.

40.03 The $\frac{1}{4}$ sec. cor. of sec. 35 only, monumented with an iron post, 1 in. diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Cor. falls northwest of the intersection of roads which bear E-W and N.

Cor. is located in E-W fence line.

S. $89^{\circ} 58'$ W., beginning new measurement.

- 40.03** The cor. of secs. 34 and 35 only, monumented with an iron post, 3 ins. diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey, from which the remaining original bearing tree

A cedar, 12 ins. diam., bears N. $51^{\circ} 40'$ W., 39 lks. dist.,
mkd. T39S R12W S34 BT.

Cor. is located 5 lks. N of E-W fence line.

West, along the S. bdy. of sec. 34.

Over rolling mountainous land, through pinon and juniper growth.

- 22.46** The closing cor. of secs. 2 and 3, T. 40 S., R. 12 W., described in the concurrent resurvey of T. 40 S., R. 12 W.

- 40.04** The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey.

Cor. is located in E-W fence line.

West, beginning new measurement.

- 20.01** Point for the W 1/16 sec. cor. of sec. 34 only, not monumented.

- 22.48** Point for the 1/4 sec. cor. of sec. 3 only, described in the concurrent resurvey of T. 40 S., R. 12 W.

- 40.02** The cor. of secs. 33 and 34, monumented with an iron post, 3 ins. diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey.

Cor. is located in E-W fence line.

S. $89^{\circ} 55'$ W., on the S. bdy. of sec. 33.

Over broken mountainous land, through pinon and juniper growth.

- 2.49** Point for the W 1/16 sec. cor. of sec. 3 only, described in the concurrent resurvey of T. 40 S., R. 12 W.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 22.52** The closing cor. of secs. 3 and 4, described in the concurrent resurvey of T. 40 S., R. 12 W.
- 40.02** The 1/4 sec. cor. of sec. 33 only, monumented with an iron post, 1 in. diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing tree
- A pinon, 10 ins. diam., bears N. $79^{\circ} 30'$ W., 35 1/2 lks. dist.,
mkd. 1/4 S33 BT.
- N. $89^{\circ} 53'$ W., beginning new measurement.
- 22.565** Point for the 1/4 sec. cor. of sec. 4 only, described in the concurrent resurvey of T. 40 S., R. 12 W.
- 40.21** The cor. of secs. 32 and 33 only, monumented with an iron post, 3 ins. diam., 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing trees
- A pinon, 6 ins. diam., bears N. $21^{\circ} 30'$ E., 14 lks. dist.,
mkd. T39S R12W S33 BT.
- A pinon, 18 ins. diam., bears N. $67^{\circ} 45'$ W., 46 lks. dist.,
mkd. T39S R12W S32 BT.
- S. $89^{\circ} 59'$ W., along the S. bdy. of sec. 32.
- Over broken mountainous land, through pinon and juniper growth.
- 22.42** The true point for the closing cor. of secs. 4 and 5, T. 40 S., R. 12 W., described in the concurrent resurvey of T. 40 S., R. 12 W.
- 39.95** The 1/4 sec. cor. of sec. 32 only, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing tree
- A cedar, 7 ins. diam., bears N. $39^{\circ} 15'$ E., 115 lks. dist.,
mkd. 1/4 S32 BT.
- From this cor., U.S.G.S. Triangulation Station "ANDERSON", a standard brass tablet, set in cement, bears S. $39^{\circ} 50.5'$ W., 302.64 chs. dist.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 39 S., R. 12 W., Salt Lake meridian, Utah

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing trees

A pinon, 6 ins. diam., bears N. 60° E., 33 lks. dist.,
mkd. 1/4 S25 BT.

A pinon, 6 ins. diam., bears N. 12° W., 23 lks. dist.,
mkd. 1/4 S26 BT.

N. 0° 05' W., bet. secs. 25 and 26.

Over broken mountainous land, through pinon and juniper growth.

20.025 Point for the N 1/16 sec. cor. of secs. 25 and 26.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

N 1/16
S 26 | S 25
1987

40.05 The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing tree

A cedar, 14 ins. diam., bears N. 49 3/4° W., 37 lks. dist.,
37 lks. dist., mkd. T39S R12W S23 BT.

From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey.

Cor. falls in a cultivated field, set steel fence post alongside the iron post.

N. 0° 09' W., bet. secs. 34 and 35.

20.01 Point for the N 1/16 sec. cor. of secs. 34 and 35, not monumented.

40.02 The cor. of secs. 26, 27, 34, and 35, monumented with a Washington County Survey Marker, 2 1/2 in. iron post, 12 ins. above the ground, with brass cap mkd.

S 27 | S 26
S 34 | S 35
1981

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

from which an original bearing tree

A cedar, 14 ins. diam., bears S. 28° E., 105 lks. dist.,
mkd. T39S R12W S35 BT. (record, S. $23\frac{1}{2}^{\circ}$ E.)

From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 survey, and a mound of stone, W of the corner.

S. $89^{\circ} 57'$ W., bet. secs. 26 and 35.

Over rolling mountainous land, through pinon and juniper growth.

20.045 Point for the W $\frac{1}{16}$ sec. cor. of secs. 26 and 35, not monumented.

40.09 The cor. of secs. 26, 27, 34, and 35.

N. $0^{\circ} 06'$ E., bet. secs. 26 and 27.

Over broken mountainous land, through pinon and juniper growth.

20.05 Point for the S $\frac{1}{16}$ sec. cor. of secs. 26 and 27.

Set a stainless steel post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

S $\frac{1}{16}$
S 27 | S 26
1987

40.10 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing trees

A pinon, 10 ins. diam., bears East, 14 lks. dist.,
mkd. $\frac{1}{4}$ S26 BT.

A pinon, 10 ins. diam., (dead), bears S. $11\frac{1}{2}^{\circ}$ W., 19 lks. dist.,
mkd. $\frac{1}{4}$ S27 BT.

N. $0^{\circ} 01'$ W., beginning new measurement.

20.03 Point for the N $\frac{1}{16}$ sec. cor. of secs. 26 and 27, not monumented.

40.06 The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing trees

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

A cedar, 10 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ E., 51 lks. dist.,
mkd. T39S R12W S23 BT.

A cedar, 8 ins. diam., bears S. $46^{\circ} 45'$ E., 62 lks. dist.,
mkd. T39S R12W S26 BT.

A cedar, 8 ins. diam., bears S. 80° W., 109 lks. dist.,
mkd. T39S R12W S27 BT.

A cedar, 10 ins. diam., bears N. $85\frac{3}{4}^{\circ}$ W., 79 lks. dist.,
mkd. T39S R12W S22 BT.

From the cor. of secs. 23, 24, 25, and 26.

S. $89^{\circ} 57'$ W., bet. secs. 23 and 26.

Over broken mountainous land, through pinon and juniper growth.

19.995 Point for the E 1/16 sec. cor. of secs. 23 and 26.

At the corner point

Set a stainless steel post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with
brass cap mkd.

$\frac{S\ 23}{E\ 1/16\ S\ 26}$
1987

Raise a mound of stone, N of the corner.

39.99 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., set
in a mound of stone, with brass cap, mkd. as described in the official record of the
1911 survey, from which the original bearing trees

A pinon, 12 ins. diam., bears S. 58° W., 54 lks. dist.,
mkd. 1/4 S26 BT.

A cedar, 12 ins. diam., bears N. $67\frac{1}{2}^{\circ}$ W., 37 lks. dist.
mkd. 1/4 S23 Bt.

West, beginning new measurement.

20.03 Point for the W 1/16 sec. cor. of secs. 23 and 26, not monumented.

40.06 The cor. of secs. 22, 23, 26, and 27.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., hereinbefore described.

N. $0^{\circ} 08'$ W., bet. secs. 33 and 34.

Over broken mountainous land, through pinon and juniper growth.

- 16.10** Point selected for the witness cor. to the S $1/16$ sec. cor. of secs. 33 and 34.
Set a stainless steel post, 30 ins. long, 2 $1/2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W C
S $1/16$
S 33 \uparrow S 34
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

- 20.10** True point for the S $1/16$ sec. cor. of secs. 33 and 34, falls on perpendicular ledges and cannot be monumented.

- 40.20** The $1/4$ sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing trees

A pinon, 12 ins. diam., bears N. 51° E., 33 lks. dist.,
mkd. $1/4$ S34 BT.

A cedar, 12 ins. diam., bears N. 70° W., 7 $1/2$ lks. dist.,
mkd. $1/4$ S33 BT.

From the cor. of secs. 26, 27, 34, and 35.

N. $89^{\circ} 59'$ W., bet. secs. 27 and 34.

Over broken mountainous land, through pinon and juniper growth.

- 19.99** Point for the E $1/16$ sec. cor. of secs. 27 and 34.

At the corner point

Set a stainless steel post, 30 ins. long, 2 $1/2$ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

E $1/16$ $\frac{S 27}{S 34}$
1987

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS**39.98**

The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., set in a mound of stone, with brass cap, mkd. as described in the official record of the 1911 survey, from which the original bearing trees

A cedar, 8 ins. diam., bears N. 84° E., 32 1/2 lks. dist.,
mkd. 1/4 S27 BT.

A pinon, 9 ins. diam., bears S. 46° E., 31 lks. dist.,
mkd. 1/4 S34 BT.

Survey of the Subdivision of Section 26,
T. 39 S., R. 12 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 26 and 35.

N. 0° 02' E., on the N-S center line of sec. 26.

20.04

Point for the center south 1/16 sec. cor. of sec. 26, not monumented.

40.08

Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E and W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C 1/4 S 26
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

60.10

Point for the center N 1/16 sec. cor. of sec. 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S 26
C
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, S of the corner.

80.12

The 1/4 sec. cor. of secs. 23 and 26.

From the 1/4 sec. cor. of secs. 25 and 26.

**SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 59' W., on the E-W center line of sec. 26.

20.03

Point for the center E 1/16 sec. cor. of sec. 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap mkd.

$$\begin{array}{c} \text{C} \quad \frac{\text{E } 1/16}{\text{S } 26} \quad \text{C} \\ 1987 \end{array}$$
40.06

The center 1/4 sec. cor. of sec. 26.

60.08

Point for the center W 1/16 sec. cor. of sec. 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

$$\begin{array}{c} \text{C} \quad \frac{\text{W } 1/16}{\text{S } 26} \quad \text{C} \\ 1987 \end{array}$$
80.10

The 1/4 sec. cor. of secs. 26 and 27.

From the center E 1/16 sec. cor. of sec. 26.

N. 0° 02' W., on the N and S center line of the NE 1/4 of sec. 26.

20.02

Point for the NE 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NE 1/4 of sec. 26.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{NE } 1/16 \quad \text{S } 26 \\ 1987 \end{array}$$

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of the corner.

Cor. is located on the W. edge of trail road, bears SW and W.

40.04

The E 1/16 sec. cor. of secs. 23 and 26.

From the N 1/16 sec. cor. of secs. 25 and 26.

S. 89° 58' W., on the E and W center line of the NE 1/4 of sec. 26.

20.015

The NE 1/16 sec. cor. of sec. 26.

**SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.03** The center N 1/16 sec. cor. of sec. 26.
 From the point for the W 1/16 sec. cor. of secs. 26 and 35.
 N. 0° 04' E., on the N and S center line of the SW 1/4 of sec. 26.
- 20.045** Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the SW 1/4 of sec. 26.
 Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
 SW 1/16 S 26
 1987
- 40.09** The center W 1/16 sec. cor. of sec. 26.
 From the point for the center S 1/16 sec. cor. of sec. 26.
 S. 89° 58' W., on the E and W center line of the SW 1/4 of sec. 26.
- 20.03** The SW 1/16 sec. cor. of sec. 26.
- 40.06** The S 1/16 sec. cor. of secs. 26 and 27.
 From the center W 1/16 sec. cor. of sec. 26.
 North, on the N and S center line of the NW 1/4 of sec. 26.
- 20.025** True point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NW 1/4, falls on perpendicular ledges and cannot be monumented.
- 24.025** Point selected for the witness cor. to the NW 1/16 sec. cor. of sec. 26.
 Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
 W C
 NW 1/16 ↓ S 26
 1987
- Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.
- 40.05** The point for the W 1/16 sec. cor. of secs. 23 and 26.

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center N 1/16 sec. cor. of sec. 26.

S. 89° 59' W., on the E and W center line of the NW 1/4 of sec. 26.

20.025 True point for the NW 1/16 sec. cor. of sec. 26.

40.05 Point for the N 1/16 sec. cor. of secs. 26 and 27.

Survey of the Subdivision of Section 34,
T. 39 S., R. 12 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of sec. 34 only, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 03' W., on the N and S center line of sec. 34.

20.06 Point for the center S 1/16 sec. cor. of sec. 34, not monumented.

40.12 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E and W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C 1/4 S 34
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

60.10 Point for the center N 1/16 sec. cor. of sec. 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S 34
C
1987

80.08 The 1/4 sec. cor. of secs. 27 and 34.

From the 1/4 sec. cor. of secs. 34 and 35.

N. 89° 53' W., on the E and W center line of sec. 34.

20.03 Point for the center E 1/16 sec. cor. of sec. 34, not monumented.

**SURVEY OF THE SUBDIVISION OF SECTION 34,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.06 The center 1/4 sec. cor. of sec. 34.

60.10 Point for the center W 1/16 sec. cor. of sec. 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \text{C } \quad \text{S } 34 \quad \text{C} \\ 1987 \end{array}$$

80.14 The 1/4 sec. cor. of secs. 33 and 34.

From the point for the center E 1/16 sec. cor. of sec. 34.

N. 0° 06' W., on the N and S center line of the NE 1/4 of sec. 34.

19.995 Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E-W center line of the NE 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{NE } 1/16 \quad \text{S } 34 \\ 1987 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

39.99 The E 1/16 sec. cor. of secs. 27 and 34.

From the point for the N 1/16 sec. cor. of secs. 34 and 35.

N. 89° 56' W., on the E and W center line of the NE 1/4 of sec. 34.

20.01 The NE 1/16 sec. cor. of sec. 34.

40.02 The center N 1/16 sec. cor. of sec. 34.

From the point for the W 1/16 sec. cor. of sec. 34 only, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 05' W., on the N and S center line of the SW 1/4 of sec. 34.

20.08 Point for the SW 1/16 sec. cor. of sec. 34, at intersection with the E-W center line of the SW 1/4.

**SURVEY OF THE SUBDIVISION OF SECTION 34,
T. 39 S., R. 12 W., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S 34
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

40.16 The center W 1/16 sec. cor. of sec. 34.

From the point for the center S 1/16 sec. cor. of sec. 34.

N. 89° 57' W., on the E and W center line of the SW 1/4 of sec. 34.

20.03 The SW 1/16 sec. cor. of sec. 34.

40.06 The true point for the S 1/16 sec. cor. of secs. 33 and 34.

GENERAL DESCRIPTION

The land encompassed in this survey is located along the west edge of Smith Mesa, with a portion dropping into the breaks along LaVerkin and Smith Creeks. The elevations varies from about 4500 to 6000 ft. above sea level. There is pinon, juniper and some cottonwood growth along the creeks.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ferrel D. Reynolds Larry V. Judd Lewis B. Roberts	Surveying Technician Cadastral Surveyor Survey Aid

CERTIFICATE OF SURVEY

I, *Richard A. Zaninovich*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *30th day of March, 1987*, I have *dependently resurveyed portions of the south boundary and subdivisional lines and surveyed the subdivision of sections 26 and 34 in T. 39 S., R. 12 W.,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 29, 1989

Date


(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the south boundary and subdivisional lines and the survey of the subdivisions of sections 26 and 34, Township 39 South, Range 12 West, Salt Lake Meridian, Utah,*

executed by *Richard A. Zaninovich*

having been critically examined and found correct, are hereby approved.

November 29, 1989

Date


(Chief Cadastral Surveyor, Utah State Office)